

ORDINANCE NO 50

AN ORDINANCE TO AMEND THE “BUILDING SEWERS AND CONNECTIONS” AS SET FORTH IN SECTION IV PARAGRAPH F OF ORDINANCE NO 48 OF THE VILLAGE OF DECATUR, MICHIGAN, ENTITLED, “AN ORDINANCE REGULATING THE USE OF PUBLIC AND PRIVATE SEWERS AND DRAINS, THE INSTALLATION AND CONNECTION OF BUILDING SEWERS, AND THE DISCHARGE OF WATERS AND WASTES INTO THE PUBLIC SEWER SYSTEM: AND PROVIDING PENALTIES FOR VIOLATIONS OF SECTIONS THEREOF: IN THE VILLAGE OF DECATUR, VAN BUREN COUNTY, MICHIGAN.

THE VILLAGE OF DECATUR ORDAINS:

SECTION 1 – Paragraph F of Section IV of Ordinance No. 48 of the Village of Decatur, Michigan is hereby amended to read as follows:

F. The building sewer shall be constructed of any of the following materials:

(1.) vitrified clay pipe and fittings meeting current ASTM and National Clay Pipe institute specifications for standard or extra strength clay sewer pipe; (2.) service weight cast iron soil pipe and fittings meeting current ASTM specifications; (3) asbestos cement pipe for sewers of 6” diameter shall be Class 1500, Type II; and for 8” diameter, Class 2400, Type II, conforming to ASTM specification C-644; (4) acrylonitrile – butadiene – styrene (A. B. S.) sewer pipe and fittings conforming to ASTM tentative specifications designation D-2680-68T; (5) polyvinyl chloride (P.V.C.) and fittings conforming to ASTM specification D-2241-65 and C.S. 255-663, Type I, Grade 2; (6) plastic pipe C.S. # 228-61, provided however that same is not installed more than 10 feet below ground surface level. If installed in filled or unstable ground, the building sewer shall be of cast iron soil pipe, except that all pipes may be accepted if laid on a suitable improved bed or cradle as approved by the Superintendent.

SECTION 2 – This ordinance shall become effective immediately upon its adoption.

Adopted by the Village Council of the Village of Decatur, Michigan on this 23rd day of September, 1971.